


**Super Calendered (SC) Paper**
**Key benefits**

- SC-A with outstanding runnability in HSWO
- Low grammage
- Increased opacity – increased volume - silk

**Areas of application**

- Magazines
- Supplements
- Catalogues
- Advertising material

**Printing method**

Heatset Weboffset

**Prepress guideline**

Max. Total Area Coverage (TAC%) 280, we recommend Under Colour Removal (UCR)

**TECHNICAL TARGET VALUES\*\***

GRAMMAGE	DIN EN ISO 536	gsm	(40)	43	(45)	(47,4)
ISO Brightness R457	DIN 53145-2 / ISO 2470 D65	%	67	67	67	67
Opacity	DIN 53 146 / ISO 2471	%	88	89	90	92
Tensile force MD	DIN EN ISO 1924-2	N	35	35	35	36
Gloss Tappi UWS/LWS	DIN EN ISO 8254-1 (Lehmann Instrument)	%	35	35	35	35
Caliper/Thickness	DIN EN ISO 534	µm	39	41	43	45
Volume	DIN EN ISO 534	m <sup>3</sup> /kg	0.98	0.95	0.95	0.95
PPS-Roughness	DIN ISO 8791-4 1.0 Mpa	µ	1.3	1.3	1.3	1.3
Luminance factor Y	DIN 53140 / DIN 5033-9	%	71	71	71	71
L*	DIN EN ISO 11664 / ISO 5631 D65/10°	%	87	87	87	87
a*	DIN EN ISO 11664 / ISO 5631 D65/10°	%	-1.1	-1.1	-1.1	-1.1
b*	DIN EN ISO 11664 / ISO 5631 D65/10°	%	2.3	2.3	2.3	2.3

\*\* The values given are target values and variations occur (40) Grammages available on request

Bahnlänge (ca. in m)	g/m <sup>2</sup>	(40)	(42)	45	47
Ø 125 cm				33 500	32 000

**Reel dimensions**

- Diameters from 120 cm to 125 cm as standard
- Reel width from 40 to 432 cm

**Wrapping**

Reels are wrapped in PE-laminated kraftliner, inner endshields are of full paperboard and outer endshields of PE-coated testliner or kraftliner. Additional edge protection is attached.

**Certificates**

FSC CoC, License Code FSC®C121501  
 PEFC™ CoC, License Code PEFC/06-33-34  
 EU-Ecolabel and TCF  
 ISO 9001 quality management  
 ISO 14001 environmental management  
 OHSAS 18001 occupational health and safety management  
 ISO 50001 energy management  
 ISEGA Certificate of Compliance

 To learn more about us and our products visit [www.heinzelpaper.com](http://www.heinzelpaper.com)